



JOY OS-111 AIR TUGGER

Specifications

Tugger Model	Motor	Data based on drum 1/2 full		Net Weight lb. / kg.	Length in. / cm	Width in. / cm	Height in. / cm
		Rope Pull lb. / kg	Rope Speed fpm / mpm				
OS-111	AMP-200	16800 / 7620	40 / 12	2550 / 1157	91-1/2 / 232	44-1/2 / 113	32-3/4 / 83
OS-111A	AMP-200	16800 / 7620	40 / 12	2360 / 1071	79-1/2 / 202	43 / 109	35-3/4 / 90
OS-111B	AMP-200	16800 / 7620	50 / 15	2100 / 953	61-1/2 / 156	41-1/2 / 105	32-3/4 / 83

Rated Capacity	Max. Pull At Stall (1ST Turn Of Drum)	Air Consumption (At Max. Power)	Horse Power
100 PSIG	26,000 Lbs	580 CFM	20 HP

Rope Capacity

Rope capacity includes 20% for rough winding.				
Tugger Model	Drum Size	1/2" / 1.27cm	5/8" / 1.59cm	3/4" / 1.91cm
OS-111	48"L x 24-3/4"D	5400 ft. / 1646 m	3350 ft. / 1021 m	2500 ft. / 762 m
OS-111A	36"L x 27-3/4"D	5400 ft. / 1646 m	3350 ft. / 1021 m	2500 ft. / 762 m
OS-111B	18"L x 24-3/4"D	1900 ft. / 579 m	1240 ft. / 378 m	940 ft. / 287 m

NOTE: *STANDARD EQUIPMENT: INSTRUCTION MANUAL & PARTS LIST, REVERSING THROTTLE VALVE W/SELF-CENTERING CONTROL, HAND OPERATED TOGGLE BAND BRAKE, SAFETY DOG FOR LOCKING DRUM



NELMACO EASTERN LTD.

2355 Lasalle Blvd., Sudbury, ON P3A 2A9 Canada

Tel: 705-560-3705

Fax: 705-560-6983

Email: info@nelmaco.com Website: www.nelmaco.com

ORIGINAL EQUIPMENT & PARTS MANUFACTURER OF JOY SLUSHER/HOIST PARTS