



## SPECIFICATIONS:

### *AF-212 Joy Two Drum Slusher c/w "D" Flange Electric*

Slusher Model	H.P.	Data based on drum 1/2 full		Net Weight lb. / kg.	Length in. / cm	Width in. / cm	Height in. / cm
		Rope Pull lb. / kg	Rope Speed fpm / mpm				
AF-212	20	3300 / 1497	200 / 61	1936 / 878	63-1/2 / 161	32 / 81	27-1/2 / 70
AF-212	25	4130 / 1873	200 / 61	2031 / 921	63-1/2 / 161	32 / 81	27-1/2 / 70
AF-212	30	4950 / 2245	200 / 61	2130 / 921	63-1/2 / 161	32 / 81	27-1/2 / 70

### *AF-212 Joy Two Drum Slusher c/w PA55 Pistonair Motor*

Slusher Model	Motor	Data based on drum 1/2 full		Net Weight lb. / kg.	Length in. / cm	Width in. / cm	Height in. / cm
		Rope Pull lb. / kg	Rope Speed fpm / mpm				
AF-212	PA-55(30 HP)	4100 / 1800	175 / 53	2200 / 998	63-1/2 / 161	32 / 81	36 / 91

### *Rope Capacity*

Rope capacity includes 20% for rough winding.			
Drum Size	3/8" / 9.5mm	1/2" / 12.7mm	5/8" / 15.8mm
A	750 ft / 229m	440 ft / 134 m	285 ft / 87m

[www.nelmaco.com](http://www.nelmaco.com)



## **NELMACO EASTERN LTD.**

2355 Lasalle Blvd., Sudbury, ON P3A 2A9 Canada

Tel: 705-560-3705

Fax: 705-560-6983

Email: [info@nelmaco.com](mailto:info@nelmaco.com) Website: [www.nelmaco.com](http://www.nelmaco.com)

**ORIGINAL EQUIPMENT & PARTS MANUFACTURER OF JOY LUSHER/HOIST PARTS**