



JOY AW-80 AIR WINCH

Specifications:

AW-80 Joy Single Drum c/w AM-2 Pistonair Motor

Winch Model	Motor	Data based on drum 1/2 full		Net Weight lb. / kg.	Length in. / mm	Width in. / mm	Height in. / mm
		Rope Pull lb. / kg	Rope Speed fpm / mpm				
AW-80	AM-2	1000 / 454	40 / 12	90 / 41	21-1/4 / 540	11-5/8 / 295	17 / 432

Rated Capacity	Max. Pull At Stall (1ST Turn Of Drum)	Air Consumption (At Max. Power)	Horse Power
100 PSIG	2000 Lbs	35 CFM	1 HP

Rope Capacity

Rope capacity includes 20% for rough winding.			
Drum Size	1/4" / 6.4mm	5/16" / 7.9mm	3/8" / 9.5mm
W	280 ft / 85m	190 ft / 58m	125 ft / 38m

NOTE: *STANDARD EQUIPMENT: INSTRUCTION MANUAL & PARTS LIST,
REVERSING THROTTLE VALVE W/SELF-CENTERING CONTROL,
HAND OPERATED TOGGLE BAND BRAKE

*OPTIONAL EQUIPMENT: COLUMN CLAMP



NELMACO EASTERN LTD.

2355 Lasalle Blvd., Sudbury, ON P3A 2A9 CANADA

Tel: (705) 560-3705

Fax: (705) 560-6983

Email: info@nelmaco.com

Website: www.nelmaco.com

ORIGINAL EQUIPMENT & PARTS MANUFACTURER OF JOY SLUSHER/HOIST PARTS