



Specifications:

EW-111 Joy Single Drum c/w AMP-94 Pistonair Motor

Tugger Model	Motor	Data based on drum 1/2 full		Net Weight lb. / kg.	Length in. / cm	Width in. / cm	Height in. / cm
		Rope Pull lb. / kg	Rope Speed fpm / mpm				
EW-111	AMP-94	2200 / 998	100 / 30.5	325 / 147	26-3/4"/68	15-1/4"/39	18-1/2"/47

Rated Capacity	Max. Pull At Stall (1 st Turn Of Drum)	Air Consumption (At Max. Power)	Horse Power
100 PSIG	7100 Lbs	285 CFM	9.4 HP

Rope Capacity

Rope capacity includes 20% for rough winding.				
Drum Size	5/16" / .79 cm	3/8" / .95 cm	1/2" / 1.27 cm	5/8" / 1.59 cm
EW	580 ft / 24.4 m	400 ft / 121.9 m	230 ft. / 70.1 m	125 ft. / 38.1 m

NOTE: *STANDARD EQUIPMENT: INSTRUCTION MANUAL & PARTS LIST, REVERSING THROTTLE VALVE W/SELF-CENTERING CONTROL, HAND OPERATED TOGGLE BRAKE.

*OPTIONAL EQUIPMENT: COLUMN CLAMP, EXHAUST MUFFLER, REMOTE CONTROL THROTTLE VALVE, MARINE PROTECTIVE EPOXY PAINT.



NELMACO EASTERN LTD

2355 Lasalle Blvd., Sudbury, ON P3A 2A9 Canada

Tel: 705-560-3705

Fax: 705-560-6983

Email: info@nelmaco.com Website: www.nelmaco.com

ORIGINAL EQUIPMENT & PARTS MANUFACTURER OF JOY SLUSHER/HOIST PARTS