



**Specifications:**

***EW-111 Joy Single Drum c/w AMP-94 Pistonair Motor***

Tugger Model	Motor	Data based on drum 1/2 full		Net Weight lb. / kg.	Length in. / cm	Width in. / cm	Height in. / cm
		Rope Pull lb. / kg	Rope Speed fpm / mpm				
<b>EW-111</b>	AMP-94	2200 / 998	100 / 30.5	325 / 147	26-3/4"/68	15-1/4"/39	18-1/2"/47

Rated Capacity	Max. Pull At Stall (1 <sup>st</sup> Turn Of Drum)	Air Consumption (At Max. Power)	Horse Power
100 PSIG	7100 Lbs	285 CFM	9.4 HP

***Rope Capacity***

Rope capacity includes 20% for rough winding.				
Drum Size	5/16" / .79 cm	3/8" / .95 cm	1/2" / 1.27 cm	5/8" / 1.59 cm
EW	580 ft / 24.4 m	400 ft / 121.9 m	230 ft. / 70.1 m	125 ft. / 38.1 m

**NOTE:** \*STANDARD EQUIPMENT: INSTRUCTION MANUAL & PARTS LIST, REVERSING THROTTLE VALVE W/SELF-CENTERING CONTROL, HAND OPERATED TOGGLE BRAKE.

\*OPTIONAL EQUIPMENT: COLUMN CLAMP, EXHAUST MUFFLER, REMOTE CONTROL THROTTLE VALVE, MARINE PROTECTIVE EPOXY PAINT.



**NELMACO EASTERN LTD**

2355 Lasalle Blvd., Sudbury, ON P3A 2A9 Canada

Tel: 705-560-3705

Fax: 705-560-6983

Email: [info@nelmaco.com](mailto:info@nelmaco.com) Website: [www.nelmaco.com](http://www.nelmaco.com)

***ORIGINAL EQUIPMENT & PARTS MANUFACTURER OF JOY SLUSHER/HOIST PARTS***