



SPECIFICATIONS:

FF-211 Joy Two Drum Slusher c/w "D" Flange Electric Motor

Slusher Model	H.P.	Data based on drum 1/2 full		Net Weight lb. / kg.	Length in. / mm	Width in. / mm	Height in. / mm
		Rope Pull lb. / kg	Rope Speed fpm / mpm				
FF-211	7.5	1230 / 559	200 / 61	940 / 428	41 / 1042	25 / 635	24 / 610
FF-211	10	2000 / 908	165 / 50	980 / 449	49 / 1253	25 / 635	24 / 610
FF-211	15	2400 / 1089	200 / 61	1190 / 540	51 / 23	25 / 635	24 / 610

FF-211 Joy Two Drum Slusher c/w Pistonair Motor

Slusher Model	Motor	H.P.	Data based on drum 1/2 full		Net Weight lb. / kg.	Length in. / mm	Width in. / mm	Height in. / mm
			Rope Pull lb. / kg	Rope Speed fpm / mpm				
FF-211	PA-10	10	2000 / 908	120 / 37	1008 / 457	46 / 1168	29 / 737	24 / 610
FF-211	AMP-180	18	2500 / 1134	165 / 51	1185 / 538	47 / 1194	29 / 737	24 / 610
FF-211	AMP-200	20	2600 / 1180	240 / 73	1225 / 556	47 / 1194	29 / 737	24 / 610

Rope Capacity

Rope capacity includes 20% for rough winding.			
Drum Size	5/16" / 7.9mm	3/8" / 9.5mm	7/16" / 11.1mm
F	565 ft / 172m	385 ft / 117m	295 ft / 90m



NELMACO EASTERN LTD.

2355 Lasalle Blvd., Sudbury, ON P3A 2A9 Canada
 Tel: 705-560-3705 Fax: 705-560-6983
 Email: info@nelmaco.com Website: Nelmaco.com

ORIGINAL EQUIPMENT & PARTS MANUFACTURER OF JOY SLUSHER/HOIST PARTS