



**Specifications:**

Tugger Model	Motor	Data based on drum 1/2 full		Net Weight lb. / kg.	Length in. / cm	Width in. / cm	Height in. / cm
		Rope Pull lb. / kg	Rope Speed fpm / mpm				
<b>JHA-20</b>	AMP-94	2400/1089	120 / 37	425 / 193	29-1/4 /74	19-3/4 /50	24/61
<b>JHAL-20</b>	AMP-94	2400/1089	120 / 37	550 / 250	42-5/8 /108	19-3/4 /50	24/61
<b>JHA-40</b>	AMP-94	4300/1950	60 / 18	425 / 193	29-1/4 /74	19-3/4 /50	24/61
<b>JHAL-40</b>	AMP-94	4300/1950	60 / 18	550 / 250	42-5/8 /108	19-3/4 /50	24/61

Tugger Model	Rated Capacity	Max. Pull At Stall (1 <sup>st</sup> Turn Of Drum)	Air Consumption (At Max. Power)	Horse Power
<b>JHA</b>	100 PSIG	5200 lbs	285 cfm	9.4 HP
<b>JHAL</b>	100 PSIG	7500 lbs	285 cfm	9.4 HP

***Rope Capacity***

Rope capacity includes 20% for rough winding.			
Tugger Model	7/16" / 11.1mm	1/2" / 12.7mm	5/8" / 15.9mm
<b>JHA</b>	630 ft / 192m	400 ft / 122m	260 ft / 79m
<b>JHAL</b>	1400 ft / 427m	1020 ft / 311m	670 ft / 204m

**NOTE:** \*STANDARD EQUIPMENT: INSTRUCTION MANUAL & PARTS LIST, HOIST THROTTLE TYPE VALVE (Self Centering), TOGGLE TYPE BRAKE  
 \*OPTIONAL EQUIPMENT: SPRING SET AIR RELEASED AUTOMATIC BRAKE  
 AIR OPERATED REMOTE THROTTLE CONTROL, SAFETY DOG LOCK



**NELMACO EASTERN LTD**

2355 Lasalle Blvd., Sudbury, ON P3A 2A9 Canada  
 Tel: 705-560-3705 Fax: 705-560-6983  
 Email: [info@nelmaco.com](mailto:info@nelmaco.com) Website: [www.nelmaco.com](http://www.nelmaco.com)

**ORIGINAL EQUIPMENT & PARTS MANUFACTURER OF JOY SLUSHER/HOIST PARTS**