



Specifications:

Tugger Model	Motor	Data based on drum 1/2 full		Net Weight lb. / kg.	Length in. / cm	Width in. / cm	Height in. / cm
		Rope Pull lb. / kg	Rope Speed fpm / mpm				
JHA-20	AMP-94	2400/1089	120 / 37	425 / 193	29-1/4 /74	19-3/4 /50	24/61
JHAL-20	AMP-94	2400/1089	120 / 37	550 / 250	42-5/8 /108	19-3/4 /50	24/61
JHA-40	AMP-94	4300/1950	60 / 18	425 / 193	29-1/4 /74	19-3/4 /50	24/61
JHAL-40	AMP-94	4300/1950	60 / 18	550 / 250	42-5/8 /108	19-3/4 /50	24/61

Tugger Model	Rated Capacity	Max. Pull At Stall (1 st Turn Of Drum)	Air Consumption (At Max. Power)	Horse Power
JHA	100 PSIG	5200 lbs	285 cfm	9.4 HP
JHAL	100 PSIG	7500 lbs	285 cfm	9.4 HP

Rope Capacity

Rope capacity includes 20% for rough winding.			
Tugger Model	7/16" / 11.1mm	1/2" / 12.7mm	5/8" / 15.9mm
JHA	630 ft / 192m	400 ft / 122m	260 ft / 79m
JHAL	1400 ft / 427m	1020 ft / 311m	670 ft / 204m

NOTE: *STANDARD EQUIPMENT: INSTRUCTION MANUAL & PARTS LIST, HOIST THROTTLE TYPE VALVE (Self Centering), TOGGLE TYPE BRAKE
 *OPTIONAL EQUIPMENT: SPRING SET AIR RELEASED AUTOMATIC BRAKE
 AIR OPERATED REMOTE THROTTLE CONTROL, SAFETY DOG LOCK



NELMACO EASTERN LTD

2355 Lasalle Blvd., Sudbury, ON P3A 2A9 Canada
 Tel: 705-560-3705 Fax: 705-560-6983
 Email: info@nelmaco.com Website: www.nelmaco.com

ORIGINAL EQUIPMENT & PARTS MANUFACTURER OF JOY SLUSHER/HOIST PARTS