



JOY Single Drum Tugger/Hoist

Hoist Model	Maximum Pull At Stall (1 st turn on drum)	Rated Rope Pull @ Line Speed (drum 1/2 full)	Rope Capacities- Smooth Wind (Rope Diameter)					Net Weight lbs	
			1/4"	5/16"	3/8"	1/2"	5/8"		3/4"
AW-80	2,000 lbs.	1,000 lbs. @ 40 fpm	280'	190'	125'			90	
EW-111	7,100	2,200 @ 100	580'	400'	230'	125'		325	
JHA-20	5,200	2,400 @ 120			400'	260'		425	
JHAL-20	5,200	2,400 @ 120			1020'	670'		550	
JHA-40	7,500	4,300 @ 60			400'	260'		425	
JHAL-40	7,500	4,300 @ 60			1020'	670'		550	
LF-113	6,400	3,100 @ 125			1400'	1125'	765'	870	
JHA-60-24	11,000	7,000 @ 50			2350'	1400'	1050'	1098	
JHA-60-30	11,000	7,000 @ 50			2710'	1780'	1255'	1170	
JHAL-60	11,000	7,000 @ 50			3550'	2100'	1575'	1250	
AF-111	21,000	12,500 @ 65	(7/16" @ 1025')			1300'	800'	500'	1250
AF-112	12,500	8,100 @ 65			1900'	1300'	970'	1450	
JHA-100	21,000	10,200 @ 50			4014'	2512'	1690'	1850	
OS-111	26,000	16,800 @ 40			5400'	3350'	2500'	2550	
OS-111A	26,000	16,800 @ 40			5400'	3350'	2500'	1360	
OS-111B	26,000	16,800 @ 40			1900'	1240'	940'	2100	
OS-200	40,000	20,000 @ 50					4000'	4800	

*Rated capacity at 100 PSIG.

*Rope Pulls & Speeds can be varied on select models.



NELMACO EASTERN LTD.

2355 Lasalle Blvd., Sudbury, ON P3A 2A9 CANADA

Tel: (705) 560-3705

Fax: (705) 560-6983

Email: info@nelmaco.com

Website: www.nelmaco.com

ORIGINAL EQUIPMENT & PARTS MANUFACTURER OF JOY SLUSHER/HOIST PARTS